

GREENMAX™ Compactor **ZEUS C200**

For All Plastic Foam: **EPE/EPP/EPS/XPS/PSP**

- **Surface Melting Technology** makes an external skin around the block.
- **Screw compression technology** produces continuous logs at a ratio of 50:1.
- **Mechanical Compression Technology**, Safe, No fumes, Lower Consumption.
- **Siemens Control System** makes the operation easy and simple.
- **Famous brand components like SIEMENS, PHOENIX, NSK, etc.**
- **CE/UL/CSA standards.**



> Technical Data

ITEM	Z-C200
Total Power Consumption	33.65 kw / 45.12 hp
Crusher Power Consumption	2*4 kw / 2.68*4 hp
Production Capacity	200 kg per hour / 440 lbs per hour
Foam Compression Ratio	50:1
Compressed Foam Density	200-400 kg/m ³ / 570-1140 lbs/cubic yard
Foam Block Dimensions	380*380 (w/h) mm / 15*15 (w/h) in.
Feed Hopper Dimension	1000*650 (l/w) mm / 39*25 (l/w) in.
Dimensions	5445*750*2080(l/w/h)mm / 214*30*82(l/w/h)in
Shipping Dimensions	Main part: 3950*950*2350 (l/w/h) mm / 156*37*93 (l/w/h) in. Output chute: 1650*620*720 (l/w/h) mm / 65*24*30 (l/w/h) in.
Weight	2,000 kg / 4,400 lbs
Standard	CE / UL / CSA

Remarks: *We can design tailor-made GreenMax™ compactors according to customer's special requirements*
FREE OF CHARGE.

APPLICABLE MATERIAL:



EPE



EPP



EPS



XPS



PSP