

GREENMAX™ Compactor **POSEIDON C350**

For **PACKAGINGS: Yogurt Cups**

- Compact cups early in the process and save space and handling.
- Increase density through compacting cups rather than baling.
- Water draining function squeezes out any liquid in the cups to the water collection tray under the machine.
- Water collection tray is made of acid-resistant stainless steel to withstand the low PH in many liquids.



> Technical Data

ITEM	P-C350
Total Power Consumption	15.55 KW/ 21HP
Screw Rotation Speed	30rad/min
Screw Reduction ratio	50:1
Dimensions	5430*1100*1850 (l/w/h) mm / 214*43*73 (l/w/h) in.
Shipping Dimensions	Main part: 4100×1220×2410 (l/w/h) mm / 161×48×95 (l/w/h) in. Output chute: 1950×550×600 (l/w/h) mm / 77×22×24 (l/w/h) in.
Weight	1850 KG/ 4078 lbs
Feed Hopper Door	1240×1040×1850 (l/w/h) mm /48×41×73 (l/w/h) in.
Applicable Material	PACKAGINGS: Yogurt Cups
Feed in / hour	20000pcs/0.1L
Production Capacity	200 KG per hour / 440 lbs per hour
Bottle Volume Reduction	8:1
Standard	CE / UL / CSA

Remarks: We can design tailor-made GreenMax™ compactors according to customer's special requirements **FREE OF CHARGE.**

APPLICABLE MATERIAL:

